

PERFORMANCE TABLE

	Sako Finnfire	Anschutz 1416D	Browning A-Bolt 22
Eley Benchrest Gold			
Average Velocity at 15 ft.	1,067 fps	1,089 fps	1,101 fps
Standard Deviation	9 fps	9 fps	2 fps
Average Muzzle Energy	101 ft-lbs	105 ft-lbs	108 ft-lbs
Smallest Group at 100 yds.	0.50 in.	0.50 in.	1.00 in.
Largest Group Size	1.00 in.	0.75 in.	1.50 in.
Average Group Size	0.80 in.	0.70 in.	1.30 in.
Winchester T-22			
Average Velocity at 15 ft.	1,121 fps	1,125 fps	1,135 fps
Standard Deviation	11 fps	13 fps	18 fps
Average Muzzle Energy	112 ft-lbs	113 ft-lbs	115 ft-lbs
Smallest Group at 100 yds.	0.75 in.	0.75 in.	1.13 in.
Largest Group Size	1.25 in.	1.00 in.	2.00 in.
Average Group Size	0.95 in.	0.90 in.	1.68 in.
CCI Stingers			
Average Velocity at 15 ft.	1,567 fps	1,556 fps	1,558 fps
Standard Deviation	9 fps	21 fps	16 fps
Average Muzzle Energy	175 ft-lbs	172 ft-lbs	173 ft-lbs
Smallest Group at 100 yds.	0.75 in.	1.00 in.	1.50 in.
Largest Group Size	1.50 in.	1.25 in.	2.25 in.
Average Group Size	1.20 in.	1.10 in.	1.90 in.

Accuracy testing consisted of firing five consecutive 5-shot groups with each load.