## REMINGTON PREMIER 1100 SPORTING NO. 82846 2.75-INCH 20 GAUGE, \$1385 **GUN TESTS GRADE: B+**

We loved the 1100 Premier's fit and finish, the outstanding case, and the well-fitted Limbsaver pad. The aficionado will likely consider professional trigger work and aftermarket chokes to squeeze the potential out of the 1100. The 2.75-inch chamber will be a disqualifier for some shooters.



## **SPECIFICATIONS**

Overall Length	49.0 IN.
BARREL LENGTH	28.0 IN.
SIGHT VENT RIB; WHITE FRONT BEAD, SILVER C	ENTER BEAD
LOP	14.0 IN.
Drop @ Comb	1.5 IN.
Drop @ Heel	2.25 IN.
BUTTPLATER3 LIM	IBSAVER PAD

WEIGHT UNLOADED	8 LBS.
MAGAZINE TYPE	Tube
MAGAZINE CAPACITY	4
STEEL SHOT CAPABLE	YES
SAFETY	CROSSBOLT
Action	NICKEL PLATED STEEL
ACTION TYPE	Gas autoloader, side eject

BARREL FINISH	HIGHLY POLISHED BLUE
STOCK HIGH-GRADE GLO	SS-FINISH WALNUT, PISTOL GRIP
Сноке Рем Снок	E, BRILEY EXT. SK, IC, LM, M
TRIGGER PULL WEIGHT	6 LBS.
Warranty	2-YEAR LIMITED
TELEPHONE	(800) 243-9700
Website	WWW.REMINGTON.COM

Since around 1963, the Remington 1100 gas system has been essentially unchanged. A look at the action shows semblance to the Remington 870 pump, with a metal housing over the magazine tube attached to a twinaction-bar assembly. The metal magazine tube housing ("action bar sleeve") is driven backward by an O-ring "barrel seal" that tries to seal the exhaust gas against a pair of loose beveled washers that reside in front of action-bar drive. It is the O-ring, called the barrel seal by Remington, that is a sacrificial part. A captured O-ring wears very little. A free, dynamic O-ring as in the 1100 application can tear or wear very quickly. It's a good idea to keep half a dozen O rings in your range bag, as your 1100 is unlikely to cycle well without one.

