

PERFORMANCE TABLE

Winchester 185-gr. Silvertip	H&K USP45C	Glock 30	EAA Witness PC
Average Velocity at 15 ft.	946 fps	944 fps	962 fps
Standard Deviation	9 fps	13 fps	13 fps
Average Muzzle Energy	368 ft-lbs	366 ft-lbs	380 ft-lbs
Smallest Group at 15 yds.	1.50 inches	2.50 inches	2.88 inches
Largest Group Size	2.00 inches	3.00 inches	3.25 inches
Average Group Size	1.90 inches	2.73 inches	3.08 inches
Federal 230-gr. Hydra-Shok			
Average Velocity at 15 ft.	869 fps	856 fps	866 fps
Standard Deviation	10 fps	9 fps	7 fps
Average Muzzle Energy	386 ft-lbs	374 ft-lbs	383 ft-lbs
Smallest Group at 15 yds.	1.50 inches	2.50 inches	2.50 inches
Largest Group Size	1.88 inches	2.63 inches	3.25 inches
Average Group Size	1.68 inches	2.43 inches	2.93 inches
UMC 230-gr. Metal Case			
Average Velocity at 15 ft.	826 fps	816 fps	807 fps
Standard Deviation	9 fps	10 fps	15 fps
Average Muzzle Energy	348 ft-lbs	340 ft-lbs	333 ft-lbs
Smallest Group at 15 yds.	2.00 inches	2.00 inches	2.63 inches
Largest Group Size	2.63 inches	3.00 inches	3.50 inches
Average Group Size	2.30 inches	2.35 inches	2.98 inches
Accuracy testing consisted of five consecutive 5-shot groups with each load. fps=feet per second. ft-lbs=foot-pounds			