

SIG SAUER P250 250F-45-BSS 45 ACP, \$712

GUN TESTS GRADE: C+

The P250 required dedicated training, but it was easy to learn. Malfunctions affected its overall grade.



SPECIFICATIONS

OVERALL LENGTH	8.0 IN.
BARREL LENGTH.....	4.5 IN.
SIGHT RADIUS.....	6.5 IN.
OVERALL HEIGHT.....	5.5 IN.
FRONT STRAP HEIGHT.....	2.5 IN.
BACK STRAP HEIGHT.....	3.2 IN.
WEIGHT UNLOADED.....	27.2 OZ.
WEIGHT LOADED (11 RDS/230 GR).....	38.7 OZ.
CAPACITY	10+1
MAXIMUM WIDTH.....	1.4 IN.
GRIP THICKNESS (MAX).....	1.35 IN.
GRIP CIRCUMFERENCE (MAX).....	5.85 IN.
FRAME.....	BLACK POLYMER & STEEL
BARREL.....	STEEL
SLIDE.....	STAINLESS STEEL
GRIP.....	KNURLED POLYMER
TRIGGER PULL WEIGHT DOUBLE ACTION.....	7.5 LBS.
TRIGGER SPAN DOUBLE.....	2.8 IN.
WARRANTY.....	LIMITED LIFETIME
TELEPHONE.....	(603) 772-2302
WEBSITE.....	WWW.SIGARMS.COM
MADE IN/ASSEMBLED IN.....	PROPRIETARY/USA



Left: The compact rear sight unit was pressed into place from the rear of the slide. The hammer returned to this deeply recessed position after every shot. Note the support tabs seated inside the slide rails.

Below: The application of a multi-filament recoil spring is common to Sig Sauer pistols. But the P250's guide rod was unusual. The end that butts against the barrel lug was heavy, while the rest of the solid guide rod telescoped.

