RUGER SR-762 AUTOLOADING RIFLE NO. 5601 7.62X51 NATO/308 WIN. \$2195

GUN TESTS GRADE: B

The top end is a fine piece of equipment. The lower could use a better trigger.



			-
Action	Semi-Auto Gas Piston	Length of Pull Max.	14.75 in.
Overall Length Min/Max	34.75 in./38.0 in.	Stock Drop @ Comb	2.1 in.
Overall Height w/o Scope	e 8.0 in.	Stock Drop @ Heel	2.2 in.
Weight Unloaded	8.6 lbs.	Stock Pitch	1.2 in.
Weight Loaded	9.1 lbs.	Bedding Block/Pillars	No/No
Capacity	20+1	Rear Sight	Dual Aperture
Magazine	Staggered Column	Front Sight	Post
Barrel	Chrome Moly Steel;	Sight Radius	18 in.
16.1	12 in. Long; 1:10 in. Twist	Receiver Scope-Base Pattern	Picatinny
Metal Finish	Manganese Phosphate/	Trigger Pull Weight	10.5 lbs.
	Hardcoat Anodized	Safety	Two Position
Buttstock	Six-Position Composite	Warranty	Lifetime
Forend	Aluminum	Telephone	(603) 865-2442
Buttplate	Plastic	Website	Ruger.com
Length of Pull Min./Max.	11.5 in.	Made In	USA



Shooters rarely fit their AR-10s/ AR-15s with an extended-eyerelief scope, but it was a natural fit. Had we used a slightly lower riser, we could have easily co-witnessed (adjusted to the same point of impact) the optic and the flip-up sights. We use a Swarovski spotting scope to watch our results downrange.



Advantages of the Ruger include extra rails for the hand guard and a 19-inch-long top rail. Here we are co-witnessing the supplied backup iron sights with the self-powered Trijicon RMR dot sight that never needs batteries, and thanks to tritium power, it is always on (\$490 from Brownells).